

PART NUMBER

**KAT177475**

REV.

DATE

COMMENTS

INITIAL


**Electrical Data**

Impedance	50 $\Omega$
Frequency Range	DC - 8 GHz.
Insertion Loss	1.25 dB Max
Power	5W
Number of Ports	1 Input and 1 Output
Attenuation Range	0-69 dB in 1 dB Steps
VSWR	1.5

**Mechanical Data**

Temperature Range: -20 °C - 90 °C

Attenuation Range	Accuracy
0 - 9 dB	$\leq \pm 0.8$ dB
10 - 19 dB	$\leq \pm 1.0$ dB
20 - 49 dB	$\leq \pm 1.5$ dB
50 - 69 dB	$\leq \pm 2.0$ dB

**RoHS Compliant**

Drawing not to scale. Dimensions for reference only

Units: mm

**Konnect RF**

WWW.KONNECTRF.COM  
1-800-790-5887

PART NUMBER

**KAT177475**

DESCRIPTION

**Variable Attenuator, SMA Female, Manual**

CAGE CODE

**664U0**

SIGNATURE

X

THIS DRAWING INCLUDING THE  
DESIGNS IS THE PROPERTY OF  
KONNECT RF AND IS NOT TO  
BE USED FOR ANY PURPOSE  
WITHOUT OUR APPROVAL.