

PART NUMBER

KAT177943-XX

REV.

DATE

COMMENTS


INITIAL

Electrical Data

Impedance	50 Ω
Power Rating	50 Watts @25°C derated linearly to 0 watts @ 125°C
Peak Power	2.5kW (5 μ s pulse width, 1% duty cycle)
Frequency Range	DC-6 GHz
Attenuation Range	1-10dB \pm 0.5dB 11-20dB \pm 0.6dB 21-30dB \pm 0.8dB 40-50dB \pm 0.8dB
V.S.W.R	1.20 maximum

Mechanical Data

Temperature Range	-55°C~ +125°C
Temperature Coefficient	<0.0004 dB/dB/°C

RoHS Compliant

Drawing not to scale. Dimensions for reference only

Units: mm

Konnect RF

WWW.KONNECTRF.COM
1-800-790-5887

PART NUMBER

KAT177943-XX

DESCRIPTION

Fixed Attenuator, N Female/Female, Uni-Directional

CAGE CODE

664U0

SIGNATURE

X

THIS DRAWING INCLUDING THE
DESIGNS IS THE PROPERTY OF
KONNECT RF AND IS NOT TO
BE USED FOR ANY PURPOSE
WITHOUT OUR APPROVAL.

Component

Housing
Body
Male Contact
Female Contact

Material

Brass
Brass
BeCu

Plating

Aluminum Blacken Anodize
White Bronze
Gold
Gold