

PART NUMBER

KAT178024-XX

REV.

DATE

COMMENTS

INITIAL


Electrical Data

Impedance	50 Ω
Frequency Range	DC - 50 GHz.
Power Rating	2 Watts @ 25°C derated linearly to 0 watts @ 125°C
Peak Power	20W (5 μ s pulse width, 1% duty cycle)
Attenuation Range	1-10dB 20dB 30dB
Deviation	-1.0-1.0dB -1.0-1.2dB -1.0-1.2dB
VSWR	1.30 Maximum

RoHS Compliant

Mechanical Data

Temperature Coefficient	≤ 0.0004 dB/dB/°C
Temperature Range:	-55 °C - 125 °C



Drawing not to scale. Dimensions for reference only

Units: mm

*Substitute Attenuation Value for XX When Ordering

WWW.KONNECTRF.COM
1-800-790-5887

PART NUMBER

KAT178024-XX

DESCRIPTION

Fixed Attenuator, 2.4 Male/Female, Bi-Directional

CAGE CODE

664U0

SIGNATURE

X

THIS DRAWING INCLUDING THE
DESIGNS IS THE PROPERTY OF
KONNECT RF AND IS NOT TO
BE USED FOR ANY PURPOSE
WITHOUT OUR APPROVAL.

Component

Housing
Connector
Male Contact
Female Contact

Material

Stainless Steel
Stainless Steel
Brass
Beryllium Brass

Plating

Passivated
Passivated
Gold
Gold