

PART NUMBER

KAT178713

REV.

DATE

COMMENTS


INITIAL

RoHS Compliant

Electrical Data

Impedance 50 Ω
 Frequency Range DC - 8 GHz
 Insertion Loss ≤ 1.0 dB Max
 VSWR ≤ 1.50 Max
 Power Rating
 Average 2W
 Peak 200W (5 μ pulse width with 2% duty cycle)

Attenuation 0 - 99 dB in 1 dB steps
 Attenuation Accuracy
 ± 0.5 dB (0 - 9 dB)
 ± 1.0 dB (10 - 19 dB)
 ± 1.5 dB (20 - 49 dB)
 ± 2.0 dB (50 - 69 dB)
 ± 2.5 or 35% (70 - 99 dB)



Drawing not to scale. Dimensions for reference only

Units: mm

Konnect RF

WWW.KONNECTRF.COM
 1-800-790-5887

PART NUMBER

KAT178713

DESCRIPTION

Variable Attenuator, SMA Female Jack

CAGE CODE

664U0

SIGNATURE

X

Component

Body
 Connector
 Female Pin

Material

Aluminium
 Stainless Steel
 BeCu

Plating

Gold

THIS DRAWING INCLUDING THE
 DESIGNS IS THE PROPERTY OF
 KONNECT RF AND IS NOT TO
 BE USED FOR ANY PURPOSE
 WITHOUT OUR APPROVAL.