

PART NUMBER <div style="font-size: 24pt; font-weight: bold; text-align: center;">KAD177026</div>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 10%;">REV.</th> <th style="width: 10%;">DATE</th> <th style="width: 50%;">COMMENTS</th> <th style="width: 30%;">INITIAL</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table> <div style="text-align: right; font-weight: bold; margin-top: 10px;">RoHS Compliant</div>	REV.	DATE	COMMENTS	INITIAL				
REV.	DATE	COMMENTS	INITIAL						

Electrical Data Impedance 50 Ω Frequency Range 0-11 GHz. Working Voltage 500 VRMS Insulation Resistance 5000M ohms min. VSWR ≤ 1.20@6GHz	<div style="text-align: center; margin-bottom: 20px;"> <p>7/16-28 UNEF-2A</p> <p>1/4-36 UNS-2A</p> <p>Ø 0.126 (3.2)</p> <p>0.091 (2.3)</p> <p>0.709 (18)</p> <p>0.315 (8.0)</p> <p>1.024 (26)</p> <p>SQ 0.500 (12.7)</p> <p>SQ 0.689 (17.5)</p> </div>
Mechanical Data Temperature Range: -65 °C - 125 °C	
Environmental Data Corrosion Resistance MIL-STD-202, Method 101. Condition B. Moisture Resistance MIL-STD-202, Method 106 Thermal Shock MIL-STD-202, Method 107. Condition B. Vibration MIL-STD-202, Method 204. Condition D. Shock MIL-STD-202, Method 213. Condition I.	

Drawing not to scale. Dimensions for reference only Units: inches (mm)



WWW.KONNECTRF.COM
1-800-790-5887

PART NUMBER <div style="font-size: 24pt; font-weight: bold; text-align: center;">KAD177026</div>		DESCRIPTION <div style="font-weight: bold; text-align: center;">Adapter, Between Series, TNC Female Jack to SMA Female Jack, 4 Hole Flange Mount</div>				
CAGE CODE <div style="font-size: 18pt; font-weight: bold; text-align: center;">664U0</div>	SIGNATURE <div style="text-align: center;">X </div>	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33%; vertical-align: top;"> Component Body Center Contact Insulator </td> <td style="width: 33%; vertical-align: top;"> Material Brass BeCu PTFE </td> <td style="width: 33%; vertical-align: top;"> Plating Nickel Gold </td> </tr> </table>		Component Body Center Contact Insulator	Material Brass BeCu PTFE	Plating Nickel Gold
Component Body Center Contact Insulator	Material Brass BeCu PTFE	Plating Nickel Gold				
THIS DRAWING INCLUDING THE DESIGNS IS THE PROPERTY OF KONNECT RF AND IS NOT TO BE USED FOR ANY PURPOSE WITHOUT OUR APPROVAL.						