

PART NUMBER

KAD177285

REV.


DATE

COMMENTS

INITIAL

Electrical Data

Impedance	50 Ω
Frequency Range	DC - 18 GHz.
VSWR	1.12(-25dB) @ DC~6 GHz Max 1.21(-20dB) @ 6~18 GHz Max
voltage rating	375 VRMS
Insertion Loss	0.2dB Max
Power Handling	2 Watt
RF Leakage	< - 70 dB
Insulation Resistance	< 5000M Ω min
Contact Resistance	< 3m Ω
Working Voltage	335 VRMS max
Temperature Range	-55 $^{\circ}$ C to 155 $^{\circ}$ C

RoHS Compliant

Drawing not to scale. Dimensions for reference only

Units: inches (mm)

Konnect RF

WWW.KONNECTRF.COM
1-800-790-5887

PART NUMBER

KAD177285

DESCRIPTION

Adapter, In Series, SMA Male Plug to Male Plug, Epoxy Captivated

CAGE CODE

664U0

SIGNATURE

X

THIS DRAWING INCLUDING THE
DESIGNS IS THE PROPERTY OF
KONNECT RF AND IS NOT TO
BE USED FOR ANY PURPOSE
WITHOUT OUR APPROVAL.

Component

Body & Coupling Nut
Center Contact
Insulator

Material

Stainless Steel
Brass
PTFE

Plating

Gold
Gold