KAD177423	REV.	DATE	DESC.	INITIAL

## SPECIFICATIONS:

IMPEDANCE: 50 OHMS WORKING VOLTAGE: 500 VRMS @ SEA LEVEL FREQUENCY RANGE: 0-7 GHz INTERFACE PER MIL-STD-348A, SECTION 313.1 & 313.2

<b>I</b>		
1.075 [27.30] REF	.846 [21.50] REF	
<u>+</u>		

13	SHELL	1	BRASS	NICKEL
12	COVER	1	BRASS	NICKEL
11	WASHER	1	BRASS	NICKEL
10	RING	1	DELRIN	NONE
9	LOCK RING	1	BRASS	NICKEL
8	RETAINING RING	1	BRASS	NONE
7	GASKET	1	S.I. RUBBER	RED
6	DIELECTRIC	1	TEFLON	NONE
5	DIELECTRIC	1	TEFLON	NONE
4	PIN	1	BRASS	GOLD
3	CONTACT	1	PHOS BRONZE	GOLD
2	PRESS FIT BODY	1	BRASS	NICKEL
1	BODY	1	BRASS	NICKEL
ITEM	DESCRIPTION	QTY	MATERIAL	FINISH

<b>G</b> Konnect RF	
---------------------	--

WWW.KONNECTRF.COM 540 NW University Blvd. Ste. 109 Port Saint Lucie, Florida, 34986 1-800-790-5887

	AD177423	DESCRIPTION	IN-SERIES ADAPTER, TNC MALE to FEMALE RIGHT ANGLE
CAGE CODE	SIGNATURE	NOTES	
664U0	X		
THIS DRAWING INCLUDING THE			
DESIGNS IS THE PROPERTY OF			
KONNECT RF AND IS NOT TO			
BE USED FOR ANY PURPOSE			
WITHOUT OUR APPROVAL.			