PART NUMBER	177783			REV.	DATE	DESC.	INITIAL
Electrical Data		1			-		1
Impedance Frequency Range VSWR Contact Resistance	50 Ω DC - 34 GHz 1.04 + .006 f (f = 0 Outer 2.0mΩ Center 3.0mΩ		4 GHz				
			<u>ــــــــــــــــــــــــــــــــــــ</u>	726 (18.45))		
		→ 3.5mm -					- √ 0-36-9A
VSWR and Frequency Range Sp are for reference and are depen type and other application spec	idant on cable						
Drawing not to scale. Dimension	ns for reference only						
G Konnec	t RF		AD177783			er - In-Series - 3.5r Gemale Jack	nm
540 NW University Blv	d. Ste. 109	AGE CODE					

540 NW University Blvd. Ste. '	105
Port Saint Lucie, Florida, 3498	36
1-800-790-5887	

KA	AD177783	Female Jack to Female Jack		
CAGE CODE 664U0	SIGNATURE X	Materials		
DESIGNS IS TH KONNECT RF /	G INCLUDING THE TE PROPERTY OF AND IS NOT TO ANY PURPOSE APPROVAL.	Body Insert Center Contacts Bead	Stainless Steel Stainless Steel Be-Cu Rexolite	Passivated Passivated Gold Plated