Р	Α	R	ГΙ	۷l	Jľ	VI	В	E	ĺ

## **KAD177948**

REV.		INITIAL

**RoHS Compliant** 

#### **Materials**

SST. Corrosion-Resistant, Non Magnetic 303, per ASTM A484 and A582. Beryllium Copper per ASTM-B-196, QQ-C-530 Oxide-Noryl (tm), MIL-P-46129

### **Finish**

Center Conductors and solder components shall be plated per MIL-G-45204 Type II, Class 1 over Nickel plate per QQ-N-290. Body and Body components shall be passivated per ASTM A380

#### **Electrical Data**

Frequency VSWR Insertion Loss DC - 18 GHz

1.15 Max. @ 18 GHz .05 √Frequency

·

2.400 REF.

VSWR and Frequency Range Specifications are for reference and are dependent on cable type and other application specific conditions

Drawing not to scale. Dimensions for reference only

# **H** Konnect RF

WWW.KONNECTRF.COM 540 NW University Blvd. Ste. 109 Port Saint Lucie, Florida, 34986 1-800-790-5887

PART NUMBER	AD177948	DESCRIPTION	Precision Adapter - In-Series - TNC Male Plug to Female Jack
CAGE CODE	SIGNATURE //		
664U0	<u>x</u>		
THIS DRAWIN	IG INCLUDING THE		
DESIGNS IS T	THE PROPERTY OF		
KONNECT RF	AND IS NOT TO		
BE USED FOR	R ANY PURPOSE		
WITHOUT OU	IR APPROVAL.		