

PART NUMBER

**KCC197897**

REV.

DATE

COMMENTS




INITIAL

**RoHS Compliant****Electrical Data**

Impedance	50 $\Omega$
Frequency Range	DC - 26.5GHz.
Insertion Loss	0.005XSQRT[F(GHz)] dB Max
Voltage Rating	500 VRMS
Insulation Resistance	5,000 M $\Omega$ min
Dielectric Withstanding Voltage	750 VRMS Min
VSWR	1.4 Max

**Mechanical Data**

Durability	100 Cycles Min.
Temperature Range:	-40 °C - 125 °C
Compatible With All Standard:	IEC61169-16



Drawing not to scale. Dimensions for reference only

Units: mm

**Konnect RF**

WWW.KONNECTRF.COM  
1-800-790-5887

PART NUMBER

**KCC197897**

DESCRIPTION

**SMA Straight Male Plug, Crimp**

CAGE CODE

**664U0**

SIGNATURE

X

THIS DRAWING INCLUDING THE  
DESIGNS IS THE PROPERTY OF  
KONNECT RF AND IS NOT TO  
BE USED FOR ANY PURPOSE  
WITHOUT OUR APPROVAL.

**Cable Types:** RG-402

**Component**  
Body & Nut  
Inner Contact  
O-Ring  
Insulator

**Material**  
Brass  
Brass  
Silicone  
PTFE

**Plating**  
Non-Magnetic Gold  
Non- Magnetic Gold  
Red  
Natural