

| PART NUMBER <div style="font-size: 24pt; font-weight: bold; text-align: center;">KCC198112</div> | <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 10%;">REV.</th> <th style="width: 10%;">DATE</th> <th style="width: 40%;">COMMENTS</th> <th style="width: 40%;">INITIAL</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table> <div style="text-align: right; margin-top: 10px;">RoHS Compliant</div> <div style="margin-top: 20px;"> Electrical Data Impedance 50 Ω Frequency Range DC - 110 GHz Insulation Resistance ≥ 5,000 MΩ VSWR ≤ 1.6 </div> <div style="margin-top: 20px;"> Mechanical Data Temperature Range -55 °C - 125 °C </div> <div style="text-align: center; margin-top: 30px;"> <p>View A side Flange size diagram</p> <p>Recommended mounting screws: M2</p> </div> | REV. | DATE | COMMENTS | INITIAL | | | | |
|---|--|----------|---------|----------|---------|--|--|--|--|
| REV. | DATE | COMMENTS | INITIAL | | | | | | |
| | | | | | | | | | |

Drawing not to scale. Dimensions for reference only Units: mm

K

Konnect RF

WWW.KONNECTRF.COM
1-800-790-5887

| PART NUMBER <div style="font-size: 24pt; font-weight: bold; text-align: center;">KCC198112</div> | | DESCRIPTION 1.0mm Straight Female Jack Receptacle, Blunt Post, 2 Hole Flange Mount, Extended Teflon | | | | | | | | | | | | | |
|--|---|--|--|-----------|----------|---------|------|-----------------|------------|----------------|------------------|------|-----------|-----|--|
| CAGE CODE <div style="font-size: 24pt; font-weight: bold; text-align: center;">664U0</div> | SIGNATURE <div style="text-align: center;"> </div> | <table style="width: 100%;"> <tr> <th style="width: 33%;">Component</th> <th style="width: 33%;">Material</th> <th style="width: 33%;">Plating</th> </tr> <tr> <td>Body</td> <td>Stainless Steel</td> <td>Passivated</td> </tr> <tr> <td>Center Contact</td> <td>Beryllium Bronze</td> <td>Gold</td> </tr> <tr> <td>Insulator</td> <td>PLF</td> <td></td> </tr> </table> | | Component | Material | Plating | Body | Stainless Steel | Passivated | Center Contact | Beryllium Bronze | Gold | Insulator | PLF | |
| Component | Material | Plating | | | | | | | | | | | | | |
| Body | Stainless Steel | Passivated | | | | | | | | | | | | | |
| Center Contact | Beryllium Bronze | Gold | | | | | | | | | | | | | |
| Insulator | PLF | | | | | | | | | | | | | | |
| THIS DRAWING INCLUDING THE DESIGNS IS THE PROPERTY OF KONNECT RF AND IS NOT TO BE USED FOR ANY PURPOSE WITHOUT OUR APPROVAL. | | | | | | | | | | | | | | | |