



All Dimensions in mm [inches] Tolerance  $\pm 0.15$  [0.006]

Parameters		Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range		DC		40	40		67	GHz
Insertion Loss			6.8	7.0		7.3	7.8	dB
Isolation			12			14		dB
Input VSWR			1.4	1.8		1.4	1.8	: 1
Output VSWR			1.9	2.2		2.5	3.0	: 1
Amplitude Imbalance			0.2	0.4		0.4	0.6	dB
Phase Imbalance			3	5		5	7	deg
Power Rating	Forward Power	0.5						W
	Peak Power	5						W
Impedance		50						Ohms
Weight		0.71						Ounces
Input / Output Connectors		1.85mm - Female						
Material		Aluminum						
Finishing		Gold Plating						

### Environmental Specifications

Operational Temperature	-45°C~+85°C
Storage Temperature	-55°C~+125°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g rms (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35c, 95%RH at 40c
Shock	20G for 11msec half sine wave, 3 axis both directions