

PART NUMBER

KPD178962

REV.

DATE

COMMENTS

INITIAL


Electrical Data

Impedance	50 Ω
Frequency Range	1 ~ 18 GHz.
Insertion Loss	\leq 1.2 dB
VSWR	\leq 1.40:1
Isolation	\geq 18 dB
Amplitude Balance	\leq 0.2dB
Phase Balance	\leq 3°
Power Rating as Divider	30 Watts
Power Rating as Combiner	3 Watts

Mechanical Data

Durability	X Cycles Min.
Temperature Range:	-45 °C ~ +85 °C

RoHS Compliant



Drawing not to scale. Dimensions for reference only

Units: mm (Inches)

Konnect RF

WWW.KONNECTRF.COM
1-800-790-5887

PART NUMBER

KPD178962DESCRIPTION **Power Divider, 2 Way, SMA Female Jack**

CAGE CODE

664U0

SIGNATURE

X

Component

Housing
Female Contact
Connector

Material

Aluminum
Be Brass
Stainless Steel

Plating

Gold
Passivated

THIS DRAWING INCLUDING THE
DESIGNS IS THE PROPERTY OF
KONNECT RF AND IS NOT TO
BE USED FOR ANY PURPOSE
WITHOUT OUR APPROVAL.