	77005					
Electrical Data					RoHS	Compliant
Type Impedance Frequency Range Input Power VSWR	Bi-Directional 50 Ω DC - 3 GHz. 1,000 Watts Avg. 2,000 Watts Peak DC-1.0 GHz @ 1.20 1.0-2.4 GHz @ 1.30 2.4-3.0 GHz @ 1.40	(15.5)	TYPE N FEMA	Æ		
Mechanical Data			4.00 (101.6) REF.			
Temperature Range: Cooling	-55 °C - 125 °C 159 C.F.M. Forced Air Fan Cooled 115 VAC - 60 Hz. OR 230 VAC - 50/60 Hz (As Required)	5.31 (13.9) 4.00 (10.8) REF.	(101.8)	0	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	

G Konnect F	RF
---------------------------	----

WWW.KONNECTRF.COM 1-800-790-5887

PART NUMBER	DESCRIPTION Termination, N Male Plug
KTM177005	
CAGE CODE SIGNATURE / /	
664U0 ×	
THIS DRAWING INCLUDING THE	
DESIGNS IS THE PROPERTY OF	
KONNECT RF AND IS NOT TO	
BE USED FOR ANY PURPOSE	
WITHOUT OUR APPROVAL.	
	<u> </u>