

PART NUMBER

KTM177648

REV.

DATE

COMMENTS


INITIAL

Electrical Data

Impedance 50 Ω
 Frequency Range DC - 6 GHz.
 Input Power 15 Watts Avg @ 25°C
 (Derated Linearly to 0.5 Watts @ 125 °C)
 Peak Power 250 Watts Max
 (5uSec Pulse, .05% Duty Cycle)
 VSWR \leq 1.15 Max @ DC-3 GHz
 \leq 1.25 Max @ 3-6 GHz

Mechanical Data

Durability 500 Cycle Min
 Temperature Range: -40 °C - 125 °C

RoHS Compliant

Drawing not to scale. Dimensions for reference only

Units: mm

Konnect RF

WWW.KONNECTRF.COM
 1-800-790-5887

PART NUMBER

KTM177648

DESCRIPTION

Termination, TNC Male Plug

CAGE CODE

664U0

SIGNATURE

X

THIS DRAWING INCLUDING THE
 DESIGNS IS THE PROPERTY OF
 KONNECT RF AND IS NOT TO
 BE USED FOR ANY PURPOSE
 WITHOUT OUR APPROVAL.

Component

Body
 Center Contact
 Housing
 Insulator

Material

Brass
 Brass
 Anodized Aluminum
 PTFE

Plating

White Bronze
 Nickel