

PART NUMBER

KAT177922-XX

REV.

DATE

COMMENTS

INITIAL


Electrical Data

Impedance 50 Ω
 Frequency Range DC - 18 GHz.
 Average Power 5W average to 25 °C ambient
 Temperature, derated linearly to 0.5W @ 125°C
 Peak Power 0.5KW (5 μ s pulse width with 1% duty cycle)

RoHS Compliant

Mechanical Data

Temperature Range: -55 °C - 125 °C



Frequency Range (GHz)	Attenuation Value & Accuracy (dB)					VSWR (Max)
	1 - 9	10	20	30	40	
DC - 8	± 0.5	± 0.4	± 0.4	± 0.5	± 0.6	1.30
DC - 12.4	± 0.7	± 0.7	± 0.7	± 0.7	± 0.75	1.35
DC - 18	-0.6/+1.2	± 1	± 1.2	± 1.2	± 1.2	1.40

Drawing not to scale. Dimensions for reference only

Units: inches (mm)

Konnect RF

WWW.KONNECTRF.COM
 1-800-790-5887

PART NUMBER

KAT177922-XX

DESCRIPTION

Fixed Attenuator, N Male/Female

CAGE CODE

664U0

SIGNATURE

X

Substitute XX for dB Value

THIS DRAWING INCLUDING THE
 DESIGNS IS THE PROPERTY OF
 KONNECT RF AND IS NOT TO
 BE USED FOR ANY PURPOSE
 WITHOUT OUR APPROVAL.

Component

Connectors
 Male Pin
 Female Pin
 Housing

Material

Brass
 Brass
 BeCu
 Brass

Plating

Nickel
 Gold
 Gold
 Nickel