

PART NUMBER

KAT178352

REV.

DATE

COMMENTS

INITIAL

Electrical Data

Impedance	50 Ω
Frequency Range	DC - 6 GHz.
Insertion Loss	≤ 1.8 dB
Average Power	2 Watts @ 25°C
Peak Power	100 Watts
	(5 μ s pulse width with 2% duty cycle)
VSWR	$\leq 1.65:1$



Mechanical Data

Temperature Range: -20 °C - 85 °C

Attenuation Accuracy

± 0.5 dB	(≤ 10 dB)
± 0.8 dB or 3%	(≤ 69 dB)

RoHS Compliant

**Tolerance: X = $\pm 5\%$** **Drawing not to scale. Dimensions for reference only****Units: mm****Konnect RF**

WWW.KONNECTRF.COM
1-800-790-5887

PART NUMBER

KAT178352

DESCRIPTION

Rotary Attenuator, N Female

CAGE CODE

664U0

SIGNATURE

X

Component
 Body
 Center Contact
 Connector

Material
 Aluminum
 BeCu
 Brass

Plating
 Blue Paint
 Gold
 Nickel

THIS DRAWING INCLUDING THE
 DESIGNS IS THE PROPERTY OF
 KONNECT RF AND IS NOT TO
 BE USED FOR ANY PURPOSE
 WITHOUT OUR APPROVAL.